



Typical Inspection Data:

Density @ 20°C	0.841 g/cm ³
Viscosity @ 100°C	9.7 cSt
Viscosity @ 40°C	50 cSt
Viscosity Index	183
Viscosity CCS @ -35 °C	5500 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.08%
Colour	Brown
Flash Point	>200°C
Pour Point	-42°C

Eco-FE Plus 0W-30

Fully Synthetic

Official Approvals:

Verified by Jaguar Land Rover to meet the requirements of STJLR.03.5007

Recommended by Comma for applications requiring:

Ford WSS-M2C950-A; ACEA C2

Product Features:

- Fully synthetic, Mid-SAPS engine oil specifically developed for latest technology Ford engines from 2014 onwards, new Land Rover and Jaguar models from 2015 and 2016 onwards.
- Designed for high fuel efficiency.
- Suitable for petrol and diesel vehicles.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 10/01/23