



Xstream® G40® Antifreeze & Coolant Concentrate

Glystantin® G40® by BASF is approved by:

Audi/Bentley/Bugatti/Lamborghini/Seat/Skoda/VW vehicles built as of 2005 (TL774-G); Cummins (CES 14603); Deutz (DQC CC-14); MAN vehicles built from 12/2011 (MAN 324 Si-OAT); Mercedes Cars and Smart (MB-Approval 325.6), Mercedes Trucks (MB-Approval 325.5); Porsche (vehicles as from 2010) 911, Boxster, Cayman, Cayenne, Panamera.

This Engine Coolant Concentrate conforms to the requirements of: BS 6580:2010

Product Features:

- Ethylene glycol based antifreeze with Si-OAT (Silicated Organic Additive Technology) inhibitors.
- Protects against corrosion, overheating and freezing.
- Typical service life of up to 5 years.
- Safeguarded with bittering agent to help prevent accidental ingestion.
- To ensure correct antifreeze & coolant selection check Comma's latest application guide in store or online at www.CommaOil.com.

Directions for use:

1. Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions.
2. Pour into vehicle cooling system.
3. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook.
4. Remove spills from paintwork immediately.

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.
- Wash off any spillage on paintwork immediately.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

Shelf Life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

14-07-2017

Typical Inspection Data:

Density @ 20 °C	1.124 g/cm ³
Appearance	Clear violet liquid
Boiling point	177 °C
Reserve Alkalinity	10ml
Water Content	2.6%
Refractive Index	1.434

Protection Levels:

Xstream® G40® (%)	Approx. Protection (°C)
33	-18
50	-36
60	-52