



Typical Inspection Data:

Appearance

Black liquid

Underbody Seal

Product Features:

- Easy to use spray-on rubberised formulation which helps to prevent rust, resist salt, insulate against noise and prolong the life of treated parts.
- A coating for protecting the underside of cars.
- Prolongs the life of treated parts.

Direction of use:

1. Remove any dirt.
2. Ensure surface is dry. Use wire brush on rusted areas.
3. Shake can well before use.
4. Hold 12 inches (30 cm) from surface & apply a light coat.
5. When dry, further coats can be applied to give uniform coverage.
6. To remove from paintwork, wipe off at once with White Spirit.
7. To avoid blockage, after each use, invert can and continue to spray until clear mist is dispersed. **IMPORTANT:** Do not apply to brakes or hoses or to the engine, gearbox, exhaust system or moving parts.

Handling:

- Caution pressurised container: protect from sunlight and other heat sources.
- Refer to Material Safety Data Sheet.

Shelf Life:

- 3 years from date of manufacture.
- Manufacture date can be identified as follows:

1st Letter-Year	2nd Letter-Month	2 Numbers -Day	Time
2020	A	Jan	A
2021	B	Feb	B
2022	C	Mar	C
2023	D	Apr	D
2024	E	May	E
2025	F	Jun	F
2026	G	Jul	G
2027	H	Aug	H
2028	J	Sep	J
2029	K	Oct	K
2030	L	Nov	L
2031	M	Dec	M

Number denotes the day of the Month

Time in 24 hour format: hour and minutes e.g. 16:05

UPDATED: 30-09-2021