

Technical Data Sheet



Typical Inspection Data: Density @ 20°C 0.849 g/cm³ Viscosity @ 100°C 22.2 cSt Viscosity @ 40°C 155 cSt Viscosity Index 170 Viscosity CCS @ -25°C 6400 cP T.B.N. 10 mg KOH/g Sulphated Ash Mass 1.1% Zinc 0.12% Calcium 0.27% **Phosphorus** 0.10% Colour Brown Flash Point >200°C **Pour Point** -36°C

Pro-S 10W-60

Fully Synthetic

Recommended by Comma for applications requiring:

Recommended for applications requiring: ACEA A3/B4

Product Features:

- Fully synthetic engine oil.
- Specially developed for high performance vehicles.
- Recommended for certain Ferrari, Aston Martin and Maserati models.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 08-01-2021