



Typical Inspection Data:

Density @ 20°C	0.832 g/cm ³
Viscosity @ 100°C	8.0 cSt
Viscosity @ 40°C	40 cSt
Viscosity Index	178
Viscosity CCS @ -30°C	3500 cP
T.B.N.	8.3 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.19%
Phosphorus	0.09%
Colour	Slight Green
Flash Point	>200°C
Pour Point	-57°C

Eco-LLP 0W-20

Fully Synthetic

Recommended by Comma for applications requiring:

VW 508 00 / 509 00

Product Features:

- Designed to deliver excellent fuel economy performance according to VW 508 00/509 00 specification whilst maintaining exceptional wear protection.
- Only suitable for modern engines and not backwardly compatible.
- Recommended for the new 2.0 TFSI 140 kW and 3.0 TDI CR 160 kW VW/Audi engines.
- Suitable for extended drain (Longlife) applications.
- Low SAPS oil to meet the demands of the latest VW 508 00/509 00 specification and to protect exhaust after treatment units.
- Special oil colour and chemical marker technology to ensure use of correct and authentic product.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 16-11-2018