



## Pro-Tech 5W-30

Fully Synthetic

**Recommended by Comma for applications requiring:**

ACEA C2;  
PSA B71 2290

### Product Features:

- Fully synthetic, high performance 5W-30 low SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust after-treatment units that require an ACEA C2 grade.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at [CommaOil.com](http://CommaOil.com).

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

### Typical Inspection Data:

Density @ 20°C	0.845 g/cm <sup>3</sup>
Viscosity @ 100°C	12.1 cSt
Viscosity @ 40°C	71 cSt
Viscosity Index	169
Viscosity CCS @ -30°C	5500 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.08%
Colour	Dark Brown with a slight hint of Red
Flash Point	230°C
Pour Point	-45°C

UPDATED: 18-12-2018