



Typical Inspection Data:

Density @ 20 °C	1.075 g/cm ³
Appearance	Clear, Green

Protection Levels:

Xstream® G64® (%)	Approx. Protection (°C)
33	-18
50	-37

Xstream® G64® Antifreeze & Coolant Ready Mixed

Glystantin® G64® by BASF is approved by:

Volvo Cars TR-31854114-002, SAME – Engines, SAME – Tractors, DEUTZ-FAHR – Tractors, HÜRLIMANN – Tractors, LAMBORGHINI TRACTORS – Tractors, MAN Turbo & Diesel DEUTZ DQC CC-14 – Worldwide

Based on Coolant Concentrate that conforms to the requirements of BS 6580:2010

Product Features:

- Ready to use ethylene glycol based antifreeze and coolant with silicate based inhibitors
- Protects against corrosion, overheating and freezing
- Typical service life of up to 5 years
- Safeguarded with bittering agent to help prevent accidental ingestion
- To ensure correct antifreeze & coolant selection check Comma's latest application guide in store or online at www.CommaOil.com

Direction of use:

1. Do not dilute - pour directly into vehicle cooling system
2. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook
3. Remove spills from paintwork immediately

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried
- Wash off any spillage on paintwork immediately
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product

Shelf Life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

Created: 16/07/18

Updated: 16/07/2018.