



Typical Inspection Data:

| | |
|-----------------------|-------------------------|
| Density @ 20°C | 0.845 g/cm ³ |
| Viscosity @ 100°C | 10.0 cSt |
| Viscosity @ 40°C | 55 cSt |
| Viscosity Index | 166 |
| Viscosity CCS @ -30°C | 4500 cP |
| T.B.N. | 6.0 mg KOH/g |
| Sulphated Ash Mass | 0.49% |
| Zinc | 0.07% |
| Calcium | 0.12% |
| Phosphorus | 0.05% |
| Colour | Brown |
| Flash Point | 230°C |
| Pour Point | -42°C |

Ecolife 5W-30

Fully Synthetic

Recommended by Comma for applications requiring:

JAGUAR LANDROVER STJR.03.5005, FORD WSS-M2C934-B
ACEA C1

Product Features:

- Fully synthetic, high performance 5W-30 low SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust after-treatment units that require an ACEA C1 grade.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 16-03-2018