



## Typical Inspection Data:

Density @ 20°C	0.840 g/cm <sup>3</sup>
Viscosity @ 100°C	9.70 cSt
Viscosity @ 40°C	54 cSt
Viscosity Index	167
Viscosity CCS @ -35°C	5900 cP
T.B.N.	6.0 mg KOH/g
Sulphated Ash Mass	0.6%
Zinc	0.08%
Calcium	0.13%
Phosphorus	0.07%
Colour	Brown
Flash Point	>210°C
Pour Point	-48°C

## Eco-P 0W-30

Fully Synthetic

**Recommended by Comma for applications requiring:**

PSA B71 2312  
ACEA C2

### Product Features:

- Fully synthetic, high performance fuel-economy promoting engine oil, developed specifically for modern petrol and diesel PSA engines.
- To ensure correct oil selection use Comma's latest application guide instore or online at [www.CommaOil.com](http://www.CommaOil.com).

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 15-11-2018